

SPCT-814D

Pneumatic 1-color pad printer

Features

- Each function controlled by microprocessor for easy operation;
- 5-digit auto counter built in;
- High quality aluminium alloy is used to make structure solid and weight light;
- Ink roller is used for ink covering, so it is easy to clean, install and uninstall;
- Independent pad up/down stroke and speed adjustment;
- Auto balanced doctor blade available for efficient ink scraping;
- Printing speed adjustable to fulfil various requirements;
- "Inking twice, printing once" for thick ink film;
- Able to sweep forward/backward without lowering pad to avoid ink drying at intervals.



Printing Sample

Technical Data

- | | |
|------------------------|------------------|
| • Ink cup diameter | Φ90(mm) |
| • Plate size | 250x100(mm) |
| • Air consumption | 146(L/min) |
| • Max.substrate height | 140mm |
| • Max.printing speed | 1300psc/hr |
| • Noise (dB) | <80 |
| • Outline dimensions | 861x460x1370(mm) |
| • Weighi | 125kg |



恒暉氣動工程有限公司

Ever Bright Printing Machine Fty Ltd

地址：香港葵涌圳邊街1號南華工業大廈18樓

18/F, South China Ind Bldg., No.1 Chun Pin St., Kwai Chung, Hong Kong.

Tel: (852) 2421 8573 (8 Lines)

Fax: (852) 2489 2512, 2423 1428

<http://www.ever-bright.com>

e-mail: info@ever-bright.com